

Product Information

GOLDEN FILM AG90, AG140, AG250 CLASSIC GEAR OILS

Description

Golden Film AG Gear Oils are a range of mineral oil based lubricants, formulated without extreme pressure (EP) additives. These oils have good natural film strength, anti-foam performance and long term stability.

Applications

Golden Film AG Gear Oils are suitable for use in equipment where the manufacturer specifies a non-EP lubricant. Applications include: manual gearboxes (e.g. Eaton/Fuller, Volvo), axles, worm gear drives (e.g. GKN), oil lubricated bearings, reduction gears/hubs, chains, steering boxes, king pins, etc.

Additionally, Golden Film AG Gear Oils are safe for use in transmissions that contain phosphor-bronze components. This makes them ideal for classic and vintage cars, motorcycles, tractors, traction engines and commercial vehicles.

Performance Level

API GL1

Physical Characteristics

SAE	90	140	250
Density at 15°C	0.899	0.900	0.925
Viscosity at 100°C, cSt.	18.4	28.9	44.0
Viscosity at 40°C. cSt.	205	422	950
Viscosity Index	95	95	95
Flash Point (Open) °C	270	280	290
Pour Point, °C	-15	-10	-10

(TDS Golden Film AG Grades – 010710 Issue 2)



Certificate No. FM 21756
BS EN ISO9001

Morris Lubricants, Castle Foregate, Shrewsbury, Shropshire, SY1 2EL
Telephone (01743) 232200 Fax (01743) 353584



Certificate No. EMS 60044
BS EN ISO14001