

TECHNICAL DATA SHEET

TAURUS EURO 5 10W-40

Fully synthetic, low ash engine oil

Product code: M403

Product Description:

Taurus Euro 5 10W-40 is a heavy duty diesel engine oil that has been formulated to meet the new low SAPS criteria.

Taurus Euro 5 10W-40 is formulated from fully synthetic base stock technology and approved performance additives which offer excellent thermal stability, low volatility, consistently efficient long life performance, complete shear stability and fuel efficiency capabilities.

New additive technology ensures optimum performance of emission control equipment such as diesel particulate filters thereby ensuring continuous pollution control and minimising environmental damage.

Benefits:

Approved by Mercedes-Benz

Approved by Volvo

Approved by Renault

Approved by Mack

Suitable for Euro 4 & Euro 5 engines

Backwards compatible to older engines

Exceptional long drain capabilities

Low volatility providing reduced oil consumption and emissions

Outstanding thermal stability offering consistent long term performance

Effective environmental protection and fuel efficiency

Outstanding anti-wear and anti-corrosion properties

Excellent dispersant and acid neutralization characteristics

Complete shear stability for extended stay in grade performance

Applications:

Taurus Euro 5 10W-40 is an ultra high performance diesel engine oil designed specifically to meet the challenge of the most severe lubrication requirements of the latest European and North American heavy duty diesel engines, particularly the low emission Euro 4 and Euro 5 engines running under the extreme demands of significantly extended oil change periods together with the clean performance requirements of these standards.

Taurus Euro 5 10W-40 will provide the highest level of performance and protection in all HGV diesel engines where performance demands are severe and service periods are extended.

TECHNICAL DATA SHEET

Product Specification:

ACEA	E6, E7
API	CI-4
Mercedes-Benz	228.51 (Fully Approved)
Renault	RXD, RLD-2 (Fully Approved) RGD
MAN	M3477, M3271-1
Volvo	VDS 3 (Fully Approved)
MTU	Type 3.1
DAF	Extended Drains
Cummins	CES 20076/77
Mack	EO-N (Fully Approved), EO-M Plus
Deutz	DQC-III-10

Specific Gravity @ 15°C	0.861
Kinematic Viscosity @ 100°C (cSt)	14.2
Kinematic Viscosity @ 40°C (cSt)	96.0
Viscosity Index	152
Flash Point PMCC (°C)	220
Pour Point (°C)	-35
TBN (mg KOH/g)	10.1
Sulphated Ash (% wt)	0.98

Typical Test Data:

Health & Safety:

Please refer to the relevant health and safety data sheet, a copy of which is freely available to all of our customers.

Availability:

Taurus Euro 5 10W-40 is available in bulk road tanker deliveries, 205 litre barrels and 25 litre drums.

Issue No: e2	June 2012	Issued by: P Timmis
--------------	-----------	---------------------