

Product Information

SUPER VERSITRAC 10W/40

Description

Super Versitrac 10W/40 has been designed to cover the majority of agricultural lubrication requirements, whilst maintaining a reduced inventory. This grade is formulated with the latest additive technology and high quality mineral oils to produce a universal lubricant for tractors, combines and agricultural machinery subjected to the severest of operating conditions.

Applications

Engines: Maybe used in a wide range of 4-stroke naturally aspirated and turbocharged diesel engines, where it maintains a high level of component cleanliness and wear protection. The product circulates extremely quickly from cold as well as providing highly effective fluid films at high operating temperatures.

Hydraulics: Protects all system components, including pumps and rams, against wear and corrosion. Performs over a wide operating temperature range in a wide variety of conditions. This oil has also been designed for use in hydrostatic transmissions on equipment where a universal product is recommended by the manufacturer.

Transmissions: The versatile additive system protects the components from the effects of shock loading, particularly gear sets and bearings. This product is highly recommended for oil immersed or “wet brakes”, where it can red the tendency for the brakes to “squawk and chatter”.

Compressors: Suitable for most portable compressors.

Performance Levels

Engine:	API CG-4, MAN 271, MIL-L-2104D, MB 228.1, Ford M2C-121B
STOU:	M.F. M1139 / 1144 / 1145 (Approved), Ford M2C 159B, John Deere JDM J27, ZF TE-ML 06,07, NH No 8200 9201
Transmission and Gear:	API GL-4 / GL5, Allison C4, Cat TO-2, Low speed / High Torque
Universal Transmission:	MF M1135, John Deere J20C, Ford M2C 134D, NH-410B, Case-IH MS 1207*
Plant and Equipment:	Vickers Hydraulics, Hydrovane, Holman compair, Atlas Copco, Sunstrand

* SUITABLE FOR USE IN EQUIPMENT REQUIRING THIS QUALITY OF LUBRICANT

Physical Characteristics

SAE Grade	10W/40
Density at 15 °C	0.881
Viscosity cSt at 100 °C	13.00
Viscosity cSt at 40 °C	85.00
Viscosity Index	151.0
Flash Point (closed) °C	190
Sulphated Ash	1.3
Pour Point °C	-37
TBN	10.5
FZG Gear Test, Pass load stage	11
Vickers Pump Wear (Wt. Loss mgs)	<50

(TDS Super Versitrac 10W/40 – 010810 Issue 1)



Certificate No. FM 21756



Certificate No. EMS 60044



Certificate No. OHS 555083

Morris Lubricants, Castle Foregate,
Shrewsbury, Shropshire, SY1 2EL
Telephone (01743) 232200
Fax (01743) 353584